

In Head Display / Temperature Transmitter / Signal Conditioning

**Programming Request Form**

for

*Nanmac Series  
F7 In Head Displays with 4-20 mA  
and  
F11 4-20 mA transmitters*

Name: \_\_\_\_\_ Date: \_\_\_\_\_

Company: \_\_\_\_\_ Address: \_\_\_\_\_

Phone: \_\_\_\_\_ Ext: \_\_\_\_\_ Line 2: \_\_\_\_\_

Fax: \_\_\_\_\_ Ext: \_\_\_\_\_ City: \_\_\_\_\_ State: \_\_\_\_\_

Email: \_\_\_\_\_ Zip: \_\_\_\_\_ Country: \_\_\_\_\_

(If thermocouple input, complete below)

<b>THERMOCOUPLE</b>	
THERMOCOUPLE TYPE: <input type="checkbox"/> B <input type="checkbox"/> C <input type="checkbox"/> E <input type="checkbox"/> J <input type="checkbox"/> K <input type="checkbox"/> N <input type="checkbox"/> R <input type="checkbox"/> S <input type="checkbox"/> T	
COLD JUNCTION: _____ (On is typical) <input type="checkbox"/> On <input type="checkbox"/> Off	
JUNCTION STYLE: <input type="checkbox"/> Grounded <input type="checkbox"/> Ungrounded	

(If RTD input, complete below)

<b>RTD</b>	
RTD TYPE: <input type="checkbox"/> Pt100 <input type="checkbox"/> Pt1000 <input type="checkbox"/> Ni100 <input type="checkbox"/> Ni1000	
ALPHA CURVE: _____ (0.00385 is typical)	
NUMBER OF WIRES: <input type="checkbox"/> 3 <input type="checkbox"/> 4	

(For grounded thermocouples we recommend an isolated unit)

TEMPERATURE RANGE: _____ (For thermocouples, default equals full range in accordance with NIST )	MEASUREMENT: _____
Minimum: _____ Maximum: _____	<input type="checkbox"/> Celsius <input type="checkbox"/> Fahrenheit
(thermocouple range, <a href="http://www.nanmac.com/handbook/g9.htm#table3">http://www.nanmac.com/handbook/g9.htm#table3</a> )	

SENSOR BREAK DETECTION:		
<input type="checkbox"/> Upscale (typical)	<input type="checkbox"/> Downscale	<input type="checkbox"/> Off

Please email, fax, or mail this form to:

Nanmac Corporation  
email: **engineering@nanmac.com**  
fax: **1.508.879.5450**  
11 Mayhew St.  
Framingham, MA 01702

Signature: \_\_\_\_\_