

PRODUCT INFO SHEET

Nanmac Corporation

Quality • Performance • Solutions

Thermowells Limited Space for 1/4" Diameter Elements A29 Series

These thermowells are used where short insertion lengths are required, as in short legs of tee, etc. Available in stainless steel SS 304, SS 316, brass ASTM-B16, carbon steel C-1020, and monel. Choice of 1/2 inch NPT, 3/4 inch NPT, or one inch NPT external threads.

NOTES:

- On 1/2 inch NPT external threads, the "U" dimension becomes one inch to accommodate the 1/2 inch NPSM female thread.
- Stainless steel or brass compression fittings are available for mounting probes into these thermowells.
- The (brass cap - BRcap) and chain is available for keeping well bore clean when not in use. If cap and chain is desired add BRcap to the part number.
- If (stainless steel - SScap) and chain is desired, add SScap to the part number.
- Order by part number as indicated



Specifications			
Part No.	Material	Exterior Thread P	Maximum Fluid Velocity (feet per second)
A29-1	SS 304	1/2" NPT	300
A29-2	SS 316		300
A29-3	Brass		207
A29-4	C-1020		290
A29-5	Monel		261
A29-6	SS 304	3/4" NPT	300
A29-7	SS 316		300
A29-8	Brass		207
A29-9	C-1020		290
A29-10	Monel		261
A29-11	SS 304	1" NPT	300
A29-12	SS 316		300
A29-13	Brass		207
A29-14	C-1020		290
A29-15	Monel		261

PO Box 6640
1657 Washington St., Bldg. 3
Holliston MA 01746
www.Nanmac.com
engineering@nanmac.com

Foremost in Temperature Measurement™
NANMAC

US & Canada: 1.800.786.4669
International: 1.508.872.4811
Fax: 1.508.879.5450
info@nanmac.com