

PRODUCT INFO SHEET

Nanmac Corporation

Quality • Performance • Solutions

RTD Cable Assemblies A8H-RTD Series

Our RTD cable assemblies feature either fiberglass (FIB) insulation rated at 900 degrees Fahrenheit or teflon (TEF) insulation rated at 400 degrees Fahrenheit. Available in two, three, or four conductors. The standard plugs and jacks are rated to a continuous 400 degrees Fahrenheit.

NOTES:

- For (HT - high temperature) plugs and jacks rated to 800 degrees Fahrenheit, specify by adding the suffix HT.
- Standard "Y" length is 36 inches \pm 1 inch; if your length requirement is different, please specify. The pigtails use teflon shrink tubing.
- Custom design units are available; contact the factory with your specific requirement.
- When ordering, specify part number and length. *Example: A8H-RTD-31-72 specifies a 3 wire fiberglass insulated assembly with standard plug and jack, 72 inches long.*

Specifications			
Dimension Drawings	Part No.	Number of Wires	Type
	A8H-RTD-10 A8H-RTD-11 A8H-RTD-12 A8H-RTD-13 A8H-RTD-14 A8H-RTD-15	2 3 4 2 3 4	FIB FIB FIB TEF TEF TEF
	A8H-RTD-20 A8H-RTD-21 A8H-RTD-22 A8H-RTD-23 A8H-RTD-24 A8H-RTD-25	2 3 4 2 3 4	FIB FIB FIB TEF TEF TEF
	A8H-RTD-30 A8H-RTD-31 A8H-RTD-32 A8H-RTD-33 A8H-RTD-34 A8H-RTD-35	2 3 4 2 3 4	FIB FIB FIB TEF TEF TEF

PO Box 6640
 1657 Washington St., Bldg. 3
 Holliston MA 01746
 www.Nanmac.com
 engineering@nanmac.com

Foremost in Temperature Measurement™
NANMAC

US & Canada: 1.800.786.4669
 International: 1.508.872.4811
 Fax: 1.508.879.5450
 info@nanmac.com